



**UPTON**

# BENTHONE GREASE

**NLGI 2,3**

*High Performance Grease*

## HI-TEMP BENTONE GREASE NLGI 2, 3

### DESCRIPTION AND FEATURES

**UPTON BENTONITE GREASE**, the benton grease has especially been developed for lubricating machines operating under high working temperatures. UPTON bentonite grease recommended for lubrication of slow moving mechanisms at high temperature, hot air, blower bearings, kiln car bearings, textile drying machine bearing, can be safely used in the range at 0-180 °C

### PERFORMANCE BENEFITS

1. Excellent resistance against water, oxidation and air moisture.
2. Prevent wear, rust and corrosion.
3. Suitable for application in operating very high temperature.
4. High pressure, irregular shocking loads.
5. Long life for the lubricated parts and low maintenance costs.
6. Non melting



Distributor Tunggal  
PT. SOKKA MULIA ABADI  
e-mail : [sokkamulia@uptonlube.com](mailto:sokkamulia@uptonlube.com)  
[www.uptonlube.com](http://www.uptonlube.com)

### UPTON LUBRICANTS

Manufactured Under ISO 9001-2015  
Quality Management System BVQI No. 235093  
Produced By :  
PT. AMAN PELUMAS NUSANTARA  
SFB Blok MM No. 16 Kawasan Industri  
Jababeka Tahap II Cikarang Bekasi - 17530

UPTONE CALCIUM BENTONITE GREASE

Characteristics	ASTM	Bentonite 2	Bentonite 3
NLGI GRADE	Grade	2	3
Soap Type		Non Soap	Non Soap
Color	Visual	Amber	Amber
Dropping Point, °C	D 2265	284	284
Penetration (1/10mm)	D 217	265-295	220-250
Water wash out @80°C loss max	D 1264	1.1	1.1
Four Ball Wear, Scar mm	D 2266	0.434	0.465
Four Ball EP ,Weld Point	D 2596	250	250

