# **Material Safety Data Sheet**



# 1. Product and company identification

Product name Transcal LT MSDS # 402664

Historic MSDS #: 0000001739 Code 402664-BE02

Product use Heat-transfer medium.

For specific application advice see appropriate Technical Data Sheet or consult our company

representative.

Manufacturer Castrol Industrial North America, Inc.

150 W. Warrenville Road Naperville, IL 60563

Supplier Wakefield Canada, Limited

3620 Lakeshore Blvd West Toronto, Ontario, Canada

M8W 1P2

Castrol Industrial North America, Inc.

150 W. Warrenville Road Naperville, IL 60563

Product Information: +1-877-641-1600

EMERGENCY SPILL INFORMATION:

1 (613) 996-6666 CANUTEC (Canada)

### 2. Hazards identification

Physical state Liquid.

Color Yellow. [Light]
Emergency overview CAUTION!

MAY CAUSE RESPIRATORY TRACT, EYE AND SKIN IRRITATION.

Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis. In accordance with good industrial hygiene and safety work practices, airborne exposures should be controlled to the lowest extent practicable. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Keep container tightly closed and sealed until ready for use. Wash

thoroughly after handling.

Routes of entry Dermal contact. Eye contact. Inhalation. Ingestion.

Potential health effects

Eyes May cause eye irritation.

Skin May cause skin irritation.

**Inhalation** May cause respiratory tract irritation.

Ingestion Ingestion may cause gastrointestinal irritation and diarrhea.

See toxicological information (section 11)

Product name Transcal LT Product code 402664-BE02 Page: 1/5

Version 1 Date of issue 10/26/2010. Format Canada Language ENGLISH.

(Canada) (ENGLISH)

# 3. Composition/information on ingredients

Ingredient name CAS # %

Base oil - highly refined Varies 95 - 100

### 4. First aid measures

Eye contact In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical

attention if symptoms occur.

Skin contact Immediately wash exposed skin with soap and water. Remove contaminated clothing and shoes.

Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if

symptoms occur.

**Inhalation** If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult,

give oxygen. Get medical attention.

Ingestion Do not induce vomiting unless directed to do so by medical personnel. Never give anything by

mouth to an unconscious person. If potentially dangerous quantities of this material have been

swallowed, call a physician immediately. Get medical attention if symptoms occur.

# 5. Fire-fighting measures

Flash point Open cup: >140°C (>284°F) [Cleveland.]

Fire/explosion hazards In a fire or if heated, a pressure increase will occur and the container may burst.

Extinguishing media

Suitable Use an extinguishing agent suitable for the surrounding fire.

Not suitable Do not use water jet.

Fire-fighting procedures Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire.

No action shall be taken involving any personal risk or without suitable training.

Hazardous combustion products

Combustion products may include the following:

carbon oxides (CO, CO<sub>2</sub>) (carbon monoxide, carbon dioxide)

Protective clothing (fire) Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus

(SCBA) with a full face-piece operated in positive pressure mode.

### 6. Accidental release measures

Personal precautions No action shall be

No action shall be taken involving any personal risk or without suitable training. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. In accordance with good industrial hygiene and safety work practices, airborne exposures should be controlled to the lowest extent practicable. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see

section 8).

Environmental precautions

Small spill

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers,

waterways, soil or air).

Methods for cleaning up

Large spill Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent

entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to lead so what is a linear of which a linear disposal according to lead to the container of th

disposal according to local regulations (see section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.

Note: see section 1 for emergency contact information and section 13 for waste disposal.

Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if watersoluble or absorb with an inert dry material and place in an appropriate waste disposal container.

Dispose of via a licensed waste disposal contractor.

Product name Transcal LT Product code 402664-BE02

Version 1 Date of issue 10/26/2010. Format Canada Language ENGLISH.

(Canada) (ENGLISH)

Page: 2/5

# Handling and storage

Handling Put on appropriate personal protective equipment (see section 8). Workers should wash hands

and face before eating, drinking and smoking. Do not breathe vapor or mist. Do not ingest. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Wear appropriate

respirator when ventilation is inadequate.

Storage Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-

ventilated area, away from incompatible materials (see section 10). Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate

containment to avoid environmental contamination.

# 8. Exposure controls/personal protection

Occupational exposure limits

Ingredient name Occupational exposure limits

Base oil - highly refined ACGIH (United States).

TWA: 5 mg/m³ 8 hour(s). Form: Mineral oil, mist

While specific OELs for certain components may be shown in this section, other components may be present in any mist, vapor or dust produced. Therefore, the specific OELs may not be applicable to the product as a whole and are provided for guidance only.

Control Measures Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist,

use process enclosures, local exhaust ventilation or other engineering controls to keep worker

exposure to airborne contaminants below any recommended or statutory limits.

Hygiene measures Wash hands, forearms and face thoroughly after handling chemical products, before eating,

smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before

reusing.

Personal protection

Eyes Avoid contact with eyes. Safety glasses with side shields or chemical goggles.

Skin and body Avoid contact with skin and clothing. Wear suitable protective clothing.

Respiratory Use adequate ventilation. In accordance with good industrial hygiene and safety work practices,

airborne exposures should be controlled to the lowest extent practicable.

**Hands**The correct choice of protective gloves depends upon the chemicals being handled, the conditions

of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and

with a full assessment of the working conditions.

Consult your supervisor or Standard Operating Procedure (S.O.P) for special handling instructions.

# 9. Physical and chemical properties

Physical state Liquid.

Color Yellow. [Light]
Odor Petroleum [Slight]
Odor threshold Not available.

Flash point Open cup: >140°C (>284°F) [Cleveland.]

Specific gravity

Not applicable.

PH

Not available.

Viscosity Kinematic: 8 mm<sup>2</sup>/s (8 cSt) at 40°C

Boiling point / Range Not available.

Melting point / Range Not available.

Product nameTranscal LTProduct code402664-BE02Page: 3/5Version 1Date of issue 10/26/2010.Format CanadaLanguage ENGLISH.

(Canada) (ENGLISH)

Vapor pressure Not available. Vapor density Not available. **Evaporation rate** Not available. Solubility insoluble in water.

LogK<sub>ow</sub>

# 10. Stability and reactivity

Stability and reactivity The product is stable.

Possibility of hazardous

reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid Avoid all possible sources of ignition (spark or flame).

Incompatibility with various substances

Reactive or incompatible with the following materials: oxidizing materials.

**Hazardous decomposition** 

products

Under normal conditions of storage and use, hazardous decomposition products should not be

produced.

**Hazardous polymerization** Under normal conditions of storage and use, hazardous polymerization will not occur.

# 11. Toxicological information

#### Other information

#### Potential chronic health effects

Carcinogenicity No known significant effects or critical hazards. Mutagenicity No known significant effects or critical hazards. **Teratogenicity** No known significant effects or critical hazards. **Fertility effects** No known significant effects or critical hazards. No known significant effects or critical hazards. Reproductive effects

**Medical conditions** aggravated by overNone known.

### 12. Ecological information

#### **Ecotoxicity**

exposure

No testing has been performed by the manufacturer.

Persistence/degradability Inherently biodegradable

**Mobility** Spillages may penetrate the soil causing ground water contamination.

Bioaccumulative potential This product is not expected to bioaccumulate through food chains in the environment.

Other ecological Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer information could also be impaired.

### 13. Disposal considerations

Waste information The generation of waste should be avoided or minimized wherever possible. Empty containers or

liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil,

waterways, drains and sewers.

NOTE: The generator of waste has the responsibility for proper waste identification (based on characteristic(s) or listing), transportation and disposal

**Product name** Transcal LT **Product code** 402664-BE02 Page: 4/5 Language ENGLISH. Version 1 Date of issue 10/26/2010. **Format Canada** (ENGLISH) (Canada)

# 14. Transport information

Not classified as hazardous for transport (DOT, TDG, IMO/IMDG, IATA/ICAO)

# 15. Regulatory information

WHMIS (Canada) Not controlled under WHMIS (Canada).

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

#### Inventories

Canada inventory All components are listed or exempted.

United States inventory All components are listed or exempted.

(TSCA 8b)

Europe inventory

Australia inventory (AICS)

China inventory (IECSC)

Japan inventory (ENCS)

Korea inventory (KECI)

All components are listed or exempted.

(PICCS)

### 16. Other information

Label requirements CAUTION!

MAY CAUSE RESPIRATORY TRACT, EYE AND SKIN IRRITATION.

History

**Date of issue** 10/26/2010.

Date of previous issue No previous validation.

Prepared by Product Stewardship

#### Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from us.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken.

Product nameTranscal LTProduct code402664-BE02Page: 5/5Version 1Date of issue10/26/2010.Format CanadaLanguage ENGLISH.(Canada)(ENGLISH)