

## PLUTUS TURBO – TURBINE OIL

### KETERANGAN PRODUK

**PLUTUS TURBO** merupakan minyak pelumas Turbin berkualitas premium, tahan terhadap oksidasi dan memiliki sifat antibusa dan demulsibilitas yang baik. Terbuat dari bahan dasar jenis paraffinic dan paket aditif yang berkualitas, mempunyai sifat tahan karat dan korosi yang baik dan stabil pada temperatur tinggi.

### KUALITAS :

**PLUTUS TURBO** Turbine Oil memenuhi standar yang dipersyaratkan seperti Cincinnati Machine P-38,P-55,P-54 dan P-57,GEK-32568F, Solar Turbines ES9-224,U.S.MilitaryMIL-H-17672D,DIN51524 Part I,Hagglunds Denison HF-1 dan HF-0, tersedia dalam beragam kekentalan, ISO VG 32, 46, 68, 100, 150, 220.

### KEGUNAAN :

**PLUTUS TURBO** Turbine Oil direkomendasikan untuk semua jenis type gas turbine, steam-turbine, R&O Hydraulic systems, vacuum pumps, line lubricators, circulating systems, bearing systems, rotary and reciprocating compressors and pumps.

### SIFAT\_SIFAT :

<b>PLUTUS TURBO TURBINE OIL</b>	<b>ISO VG 32</b>	<b>ISO VG 46</b>	<b>ISO VG 68</b>	<b>ISO VG 100</b>	<b>ISO VG 220</b>
Kinematic Viscositty @ 40°C, cSt	31.5	46	68	100	220
@ 100°C, cSt	5.4	6.8	8.2	10.6	18
Viscosity Index	108	103	99	96	96
Flash Point, °C (PMCC)	215	220	224	230	270
Pour Point, °C	-15	-15	-13	-13	-9

**Kemasan : Drum isi 200 liter & Pail isi 20 liter**