

AGIP DIESEL SIGMA is an API CD/SF, MIL-L-2104 D lubricant for high output diesel engines including supercharged units. It is formulated from high quality base stock of high viscosity index treated with a large percentage of additives to impart superior detergency together with high dispersant, antioxidant, antiwear and antifoam properties.

The SAE grade 10W is also suitable to be employed in hydraulic circuits of various equipments (earthmovers, loaders, etc) where an engine oil of such a viscosity grade is prescribed.

CHARACTERISTICS (TYPICAL FIGURES) AGIP DIESEL SIGMA

Characteristics	ASTM	Unit	SAE GRADE			
			10W	30	40	50
Density at 15°C	D 4052	kg/l	0.875	0.887	0.892	0.898
Viscosity at 100°C	D 445	mm ² /s	6.5	11.6	15.6	19.8
Viscosity at 40°C	D 445	mm ² /s	40.8	98.6	154	222.8
Viscosity Index	D 2270		111	106	103	102
Flash Point, COC	D 92	°C	224	246	268	274
Pour Point	D 97	°C	-30	-18	-15	-9
Base Number	D 2896	mgKOH/g	5	11	11	11

PROPERTIES AND PERFORMANCES

- AGIP DIESEL SIGMA has superior detergency and is particularly suitable for supercharged diesel engines. It also has good dispersant properties. The lubricant thus minimizes the formation of lacquer and varnish, as well as sludge and other engine deposits; helps prevent ring sticking, and keep pistons clean while maintaining potential deposits in suspension.
- Its anticorrosion properties effectively protect the engine from corrosion by combustion moisture and acids.
- Its anti-wear properties ensure long life of moving parts and greatly reduce the need for engine servicing and overhauls.
- It has marked resistance to deterioration, especially that caused by oxidation due to prolonged high-temperature operation in the presence of air and other agents.
- Its antifoam properties prevent the formation of air bubbles that could adversely affect lubricant film continuity.

SPECIFICATIONS

AGIP DIESEL SIGMA is officially approved or meets the requirements of the following service and specifications:

- API SERVICE CD/SF
- MIL – L – 2104 D level
- CATERPILLAR TO-2
- ALLISON C-3

APPLICATION

AGIP DIESEL SIGMA is specifically designed and formulated for :

- 4 stroke diesel engines, includes supercharged, turbocharged and heavy equipment engines such as bulldozer, wheel loader, motor grader, tractors etc.
- Static and marine diesel engines.
- Hydraulic system for heavy equipment, dump truck, forklift etc. (Sigma 10W)
- Transmission and Gear to fulfill Allison C3 and OEM requirement.
- 4 stroke gasoline engine requiring API SF performance level.