

UPTON DIESEL ENGINE OIL

High Quality Lubricants
S Series



Distributor Tunggal
PT. SOKKA MULIA ABADI
e-mail : sokkamulia@uptonlube.com
www.uptonlube.com

High Performance Diesel Engine OIL

Industrial high-performance diesel engine Recommended for diesel engines and other heavy-duty engines that require API CF / SF lubricants, can also be used on long-haul vehicles or vehicles with a constant speed of the like. Also equipped with extra protection against corrosion and wear.

Characteristics	UPTONE DIESEL ENGINE OIL S series				
	ASTM	10W CF	30 CF	40 CF	50 CF
Density at 15°C/kg/l	D1298	0.883	0.892	0.8953	0.900
Kinematic Viscosity 40°C cSt	D445	41	111.3	143	235.5
Kinematic Viscosity 100°C cSt	D445	6.6	12.7	15.7	19.8
Viscosity Index	D2270	114	106	113.8	96.3
Flash Point	D92	232	236	248	250
Base Number (TBN)	D2896	11.2	11.16	11.16	11.3
Pour Point ,°C	D97	-10	-12	-12	-9
Foaming Characteristic	D892				
Sequence I		0/0	0/0	0/0	10/0
Sequence II		0/0	0/0	0/0	0/0
Sequence III		0/0	0/0	0/0	0/0

UPTON LUBRICANTS

Manufactured Under ISO 9001-2015
Quality Management System BVQI No. 235093

Produced By :
PT. AMAN PELUMAS NUSANTARA
SFB Blok MM No. 16 Kawasan Industri
Jababeka Tahap II Cikarang Bekasi - 17530

